



STUCCO ITALIANO SRL

Via dell'Artigianato 7, Sarcedo 36030 - Italia
Tel. +39 347 2469500 e-mail: info@stuccoitaliano.it

NORMAL PRIMER

1

PRIMER FOR LIME BASED PRODUCT

Description	Special primer for lime-based products
Composition	Special acrylic polymer, water, special additives.
Colours	Transparent
Appearance	Opaque, slightly rough

Type of Surface to be Covered

New plaster
Gypsum
Plasterboard
Medium density wood

Old old plaster
washable paint

Use as a primer for Marmorino Veneziano, Lime Paint, Intonachino .

Application	by hand with brush or roller
-------------	------------------------------

Packaging	Lt. 10 polyethylene containers and Lt. 1 polyethylene containers
-----------	--



STUCCO ITALIANO SRL

Via dell'Artigianato 7, Sarcedo 36030 - Italia
Tel. +39 347 2469500 e-mail: info@stuccoitaliano.it

Dilution	600 – 900% with water.	2
Theoretical Yield	- gr/mq. 150 / 200 oz/ft ² 0.49 – 0.66	
Drying	1 hours at 20°C (68°F) to the touch 18 hours at 20°C (68°F) below the surface	
Application Temperatures	min. 5°C (41°F) max 30°C (86°F) - R.U. < 85 % ca.	
Specific weight	1.480 ± 80 (gr/l.)	
Viscosity	thixotropic	
pH after 30 days	8,0 ± 0,20	
Inflammability	non-flammable	
Shelf Life	24 months	
Storage Suggestions	Product maintains its characteristics best if protected from extreme heat or cold	
Safety Norms	Protect eyes. In case of contact with eyes or skin, rinse thoroughly with water. Keep out of reach of children.	
Disposal	Product must be disposed of according to norms and regulations in force. Containers must be recycled.	