



STUCCO ITALIANO SRL

Via dell'Artigianato 7, Sarcedo 36030 - Italia
Tel. +39 347 2469500 e-mail: info@stuccoitaliano.it

Technical Data Sheets

1

QUARTZ PRIMER – Fondo Fine

Very Adhesive Primer for Lime Based Products

Description	Special primer for lime-based products
Composition	Special acrylic polymer, fine sand of quartz, water, special additives.
Colour	Transparent
Appearance	Opaque, slightly rough
Type of Surface to be Covered	
New	plaster gypsum plasterboard medium density
Old	old plaster washable paint
Use as a primer for	Marmorino Veneziano, Lime Paint, Velvet Marmorino, Seta, Intonachino .
Application	by hand with brush or roller
Packaging	Lt. 5 w. gallon 1.32 imp. Gallon 1.1 net polyethylene containers
VOC Classification	As per Dir. 2004/42/EC, Cat. A/h: Binding primers EU limit value: 50g/l (2007), 30g/l (2010) 12 g/l of VOC
Dilution	30 – 40% with water.

Theoretical Yield	gr/mq. 150 /200, oz/ft2 0.49 – 0.66
Drying	2 hours at 20°C (68°F) to the touch 24 hours at 20°C (68°F) below the surface
Application Temperatures	min. 5°C (41°F) max 30°C (86°F) - R.U. < 85 % ca.
Specific weight	1.480 ± 80 (gr/l.)
Viscosity	thixotropic
pH after 30 days	8,0 ± 0,20
Inflammability	non-flammable
Shelf Life	12 months
Storage Suggestions	Product maintains its characteristics best if protected from extreme heat or cold
Safety Norms	Protect eyes. In case of contact with eyes or skin, rinse thoroughly with water. Keep out of reach of children.
Disposal	Product must be disposed of according to norms and regulations in force. Containers must be recycled.

Note: If the product has been diluted, mix often to avoid sedimentation of the quartz sand/powder.