



STUCCO ITALIANO srl

Via dell'Economia, 117- 36100 Vicenza (Vi) - Italia
e-mail: info@stuccoitaliano.it / polistena@stuccoitaliano.it Skype: stucco.italiano
C.F. / P.Iva 03744780242 REA 350312
IBAN IT30G050341180000000000847 BIC-Swift BAPPIT21127

TECHNICAL DATA SHEET

KRISTALIUM

This is a water-based acrylic finish for interiors with premium, high-quality glitter and fine glass granules that randomly accumulate to give off special decorative effects.

Applied with a spalter; it can be colored in any color. It's extremely washable.

| | |
|-----------------------------|---|
| Application | by hand, with a brush on our Quartz Primer |
| Dilution | Ready to use. |
| Yield | 6-8 sq.m. per liter. depending on the finish |
| Drying | 4 hours at 20°C to the touch 24 hours at 20°C below the surface |
| Application Temperatures | min. 8°C max 30°C - U.R. < 85 % ca. |
| Specific weight | 1,080 ± 40 (gr/LT.) |
| Inflammability | non-flammable |
| VOC Classification | As per Dir. 2004/ 427 EC, Cat . A/c: Paints for exterior walls of mineral substrate. Eu limit 75 g/l (2007) 40 g/l (2010). This product contains 10 g/l of Voc. |
| Shelf Life | 24 months in original packaging. |
| Packaging | 1 L. and 2,5 L. buckets. |
| Storage Suggestions | Product maintains its characteristics best if protected from extreme heat or cold. Avoid freezing. |
| Safety Norms | In case of contact with eyes or skin, rinse thoroughly with water. Keep out of reach of children. |
| Disposal | Product must be disposed of according to norms and regulations in force. Containers must be sent for recycling. |



STUCCO ITALIANO srl

Via dell'Economia, 117- 36100 Vicenza (Vi) - Italia
e-mail: info@stuccoitaliano.it / polistena@stuccoitaliano.it Skype: [stucco.italiano](https://www.skype.com/name/stucco.italiano)
C.F. / P.Iva 03744780242 REA 350312
IBAN IT30G050341180000000000847 BIC-Swift BAPPIT21127

WALL SURFACE PREPARATION

The background must be smooth. So if the wall is new make sure it is uniform and apply our Quartz Primer. On an old wall, we recommend removing all not solid paint and applying Primer Normal diluted with water 1 to 10. Then apply the plaster until the surface is perfectly smooth and apply Quartz Primer.

Note: Quartz Primer can be applied in natural white or in a color of a slightly lighter tone than the final Kristalium color.

APPLICATION

Apply the undiluted product with a brush or spalter, with short brush strokes starting from one point, then spreading it out in all directions. After applying it to an area of approximately 1 square meter, wipe the decorated surface with a dry brush, brushing the surface with strokes going in all directions. This helps to increase the decorative effect. After about 5 to 6 hours at 20 °C, you can apply the second coat in the same way, paying careful attention to go over the small accumulations of the minute glassy sand in an orderly manner. This gives the finish its unique aesthetic effect. After about 20 minutes, before it start drying, press the surface with a stainless steel spatula. This allows the glitter to spread out evenly at surface level, thus increasing the softness of the surface and the glitter effect.