

TECHNICAL DATA SHEET

SEALER _ Waterproof

Name	SEALER
Description	Waterproof and sealer for absorbent natural stone and building products such as lime- and cement-based floors which when applied makes the material water, smog and oil repellent. Treated surfaces are easy to clean. The special formulation provides excellent penetration without affecting the material's breathability or color. It is also highly resistant to UV rays. The product can be easily removed with common solvent-based detergents. Test the product on an inconspicuous area and wait at least 48 hours to assess the effectiveness of the product..
Composition	It is a fluoropolymers water-based solution.
Appearance	pale yellow liquid
Reduction of water absorption:	>70%
Type of Surface to be Covered	All vertical and horizontal surfaces where is required protection from liquid or oil. It is proper for cement and lime-based materials, stone and similar porous surfaces.
Packaging	Canister 5 liters
Dilution	Ready to use
Theoretical Yield	9-12 sq. m./litre of product on EpoFloor.
Drying time	in depth 1 hours

Application Temperatures	12 to 30°C
Specific weight	0,98
pH after 30 days	N.A.
Boiling Point	N.A.
Water solubility	Soluble
Shelf Life Disposal	It can be stored over 2 years in their original sealed packagings at temperatures between +10°C and +30°C. Refer to the product health and safety data sheet.

Instruction for application

Apply the product only on absorbent surfaces which are clean and dry. Depending on your needs, the product, which is ready-to-use, can be applied using a low-pressure spray, soft brush or roller. Apply at least two coats. For surfaces with high porosity, it is recommended to apply the product until it is completely saturated. Always apply the product uniformly avoiding puddling on the surface.

The tools can be cleaned with water.