



STUCCO ITALIANO SRL

Via dell'Economia 117, Vicenza 36100 - Italia

Tel. +39 347 2469500 e-mail: info@stuccoitaliano.it

Specification Sheet

FINE WAX

| | |
|--------------------------------|--|
| Description | A mineral wax in paste form which acts as a protective barrier against water and dirt. |
| Composition | Paraffin |
| Application fields | to protect in interior: MARMORINO VENEZIANO CLASSIC MARMORINO VENEZIANO CARRARA |
| Color | Semi-transparent white. |
| Appearance | Thick paste |
| Specific weight | 0,79 kg. / lt. |
| Inflammability | flammable. Point of flammability 45°C |
| Packaging | lt 1,0 metallic container |
| Theoretical Yield | lt 1 apply 28-30 sq/m |
| Shelf live | 48 months |
| Storage Suggestion | 0°C to 25°C |
| Application Temperature | 10° to 30°C |
| Safety Norms | Keep far for fire sources or high temperature: it is flammable. Keep out of reach of children. Frequent use can be causes of skin dryness Contains Dearomatic Hydrocarbon: protect breathing when apply it. |
| Disposal | Product must be disposed of according to norms and regulations |

in force. Containers must be recycled.

Voc: (direct. 1999/13/CE) 75,19% - 594,00 g/ l of product

APPLICATION NOTE:

For best results as a liquid and dirt repellent apply 24 hours after the stucco has been finished. Using a soft cloth or better a metal trowel.

Apply a very thin layer all over the surface. Be careful to apply a very thin layer, if lamps remain on the surface will cause stains: to reduce this risk we suggest to apply first a coat of our Bee's wax and then to use the Paraffin wax.

After seven hours from application you can buffer by hand with a soft cloth or a mechanic buffer.

It is used into the shower area and in general where is required a strong protection from water, but also where is needed a high glossy finish.